AMENDMENT TO THE CLAIMS

A listing of the claims presented in this patent application appears below. This listing replaces all prior versions and listing of claims in this patent application.

1. (Currently Amended) A host device [[for]] operative to input inputting/outputting data to to/from a storage device for storing data and output data from the storage device, the host device comprising [[:]] a controller which

divides a series of cryptographic input/output processing for encrypting data to be secured and inputting[[/]] or outputting the same into a plurality of procedures, and

issues to the storage device a command for making the storage device execute a procedure to be executed on the storage-device side out of the procedures, [[and]]

wherein the controller obtains information for estimating time necessary to execute the command from the storage device prior to the issuance of the command, sets a wait time for the command based on the obtained information, issues the command to the storage device, and waits the time set for the command before it issues a command for the next procedure to the storage device.

- 2. (Original) The host device according to claim 1, wherein the information for estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary to execute the command.
- 3. (Original) The host device according to claim 1, wherein the information for estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary for at least one basic process out of an encrypting operation, a decrypting operation, a hash operation, a random number generating operation, and log retrieval which are used to execute the command.

p.3

Application No. 10/809,789

- (Currently Amended) A storage device comprising:
- a storage medium which stores data;
- a controller which receives a command from a host device in executing a series of cryptographic input/output processing for encrypting data to be secured and inputting[[/]] or outputting the same between the storage medium and the host device, the command being issued as a result of division of the cryptographic input/output processing into a. plurality of procedures; and
 - a cryptographic processing unit which executes the command,

wherein in response to a request from the host device, the controller provides information from which the host device estimates the time necessary for the cryptographic processing unit to execute the command.

- 5. (Currently Amended) The storage device according to claim 4, wherein according to the processing procedures, the cryptographic input/output processing is divided into any of process units including:
- a process for receiving data input from the host device and performing encryption or decryption using the cryptographic processing unit if necessary;
- a process for performing encryption, decryption, or signature attachment using the cryptographic processing unit in order to output data to the host device; and
- a process for outputting data to the host device, and the command is issued by each of the process units divided.
- (Original) The storage device according to claim 4, wherein the information for 6. estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary to execute the command.
- 7. (Original) The storage device according to claim 5, wherein the information for estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary to execute the command.

- 8. (Original) The storage device according to claim 4, wherein the information for estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary for at least one basic process out of an encrypting operation, a decrypting operation, a hash operation, a random number generating operation, and log retrieval which are used to execute the command.
- 9. (Original) The storage device according to claim 5, wherein the information for estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary for at least one basic process out of an encrypting operation, a decrypting operation, a hash operation, a random number generating operation, and log retrieval which are used to execute the command.
- 10. (Original) The storage device according to claim 4, wherein the controller checks if the commands issued as a result of division of the plurality of procedures are in regular order of execution.
- 11. (Original) The storage device according to claim 5, wherein the controller checks if the commands issued as a result of division of the plurality of procedures are in regular order of execution.
- 12. (Currently Amended) A data input/output method for executing a series of cryptographic input/output processing for encrypting data to be secured and inputting[[/]] or outputting the data between a storage device for storing data and a host device, comprising:

dividing the cryptographic input/output processing into a plurality of procedures, and making the host device execute a procedure to be executed on the host-device side out of the procedures;

allowing the host device to issue a command to the storage device in order to make the storage device execute a procedure to be executed on the storage-device side;

allowing the storage device to receive the command; and allowing the storage device to execute the command,

wherein the host device obtains information for estimating time necessary for the storage device to execute the command from the storage device prior to the issuance of the command, issues the command to the storage device, and waits the time estimated necessary to execute the command before it issues a command for the next procedure to the storage device.

13. (Currently Amended) The data-input/output method according to claim 12, wherein according to the processing procedures, the cryptographic input/output processing is divided into any of process units including:

a process for receiving data input from the host device and performing encryption or decryption using the cryptographic processing unit if necessary;

a process for performing encryption, decryption, or signature attachment using the cryptographic processing unit in order to output data to the host device; and

a process for outputting data to the host device, and the command is issued by each of the process units divided.

- 14. (Currently Amended) The data-input/output method according to claim 12, wherein the information for estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary to execute the command.
- 15. (Currently Amended) The data-input/output method according to claim 13, wherein the information for estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary to execute the command.
- 16. (Currently Amended) The data-input/output method according to claim 12, wherein the information for estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary for at least one basic process out of

an encrypting operation, a decrypting operation, a hash operation, a random number generating operation, and log retrieval which are used to execute the command.

17. (Currently Amended) The data input/output method according to claim 13, wherein the information for estimation includes any one of a typical processing time, an average processing time, and a maximum processing time necessary for at least one basic process out of an encrypting operation, a decrypting operation, a hash operation, a random number generating operation, and log retrieval which are used to execute the command.